




Sail Power

Sail Power models are designed for sailboats and feature an alternator and more thrust to control larger boats.



Choke for fast and easy starts

The manual choke enriches the fuel-to-air ratio, delivering fast and easy starts, particularly when the engine is cold.



10 HOURS* of BOATING

With 9 kg
standard
Propane tank

* Approximate operating time at 5,000 rpm



Features

- 12 Volt, 4 Amp / 50-Watt charging system with cable to charge battery or other electronics
- Reverse-thrust exhaust relief hole
- 6-inch high-thrust propeller



Easy and safe fuel hose connection

Fuel hose connector threads quickly and easily to the outboard and contains a shut-off valve to safely stop the flow of propane when disconnected.

High displacement and propane fuel deliver a clean-burning, powerful and easy-to-operate portable outboard

Mercury's new 5hp FourStroke Propane outboard provides more convenience and less hassle. Now you can power your boat with the same propane used for your grill and eliminate the need to haul gasoline.

The 5 hp FourStroke Propane outboard with a large 123 cc displacement offers best-in-class power by delivering a true 5 hp – something our competition can't claim.



Reliability, Portability
and Power with the
convenience of Propane



Specifications

	5MH	5MLH	5MLHA Sail Power	5MXLHA Sail Power
HP/kW @ Prop	5 / 3.7	5 / 3.7	5 / 3.7	5 / 3.7
Max RPM (WOT)	5000 - 6000	5000 - 6000	5000 - 6000	5000 - 6000
Cylinder	1	1	1	1
Displacement	123 cc	123 cc	123 cc	123 cc
Bore & Stroke (mm)	59 x 45	59 x 45	59 x 45	59 x 45
Fuel Induction	2-Valve (OHV)	2-Valve (OHV)	2-Valve (OHV)	2-Valve (OHV)
Ignition System	CDI Ignition	CDI Ignition	CDI Ignition	CDI Ignition
Fuel System	Propane Mixer	Propane Mixer	Propane Mixer	Propane Mixer
Alternator (Amp/Watt)	Optional	Optional	4 amp / 50 Watt	4 amp / 50 Watt
Battery Charger	Optional	Optional	Standard	Standard
Cooling System	Water-cooled	Water-cooled	Water-cooled	Water-cooled
Starting	Manual	Manual	Manual	Manual
Gear Ratio	2.15:1	2.15:1	2.15:1	2.15:1
Gear Shift	F-N-R	F-N-R	F-N-R	F-N-R
Propeller	7.8 x 8"	7.8 x 8"	8.4 x 6"	8.4 x 6"
Steering	Tiller	Tiller	Tiller	Tiller
Trim Positions	6	6	6	6
Shallow Water Drive	Standard	Standard	Standard	Standard
Exhaust System	Through Prop	Through Prop	Through Prop	Through Prop
Fuel Tank	Remote	Remote	Remote	Remote
Operator Warning System	Oil Pressure, Over-rev	Oil Pressure, Over-rev	Oil Pressure, Over-rev	Oil Pressure, Over-rev
Shaft Length (in)	15	20	20	25
Shaft Length (mm)	381 (S)	508 (L)	508 (L)	635 (XL)
Dry Weight (Kg)	27,2	27,5	28,6	29,1

* Dry Weight: Lightest Version model, excludes engine oil, rigging, hardware

New
5 hp Propane
Outboard

- Runs on conventional propane, a convenient alternative to gasoline
- Eco-friendly and clean-burning with 30 % lower exhaust emissions compared to gasoline
- Auto propane-shutoff valve on outboard for safety
- Light and portable, starting at just 27 kg
- No fuel priming required
- Manual choke for fast, reliable starts
- Easy-to-reach shift lever

